



Request for Reconditioning

MUST ACCOMPANY ALL ORDERS

Phone: 714-632-3000 Fax: 714-632-3003

1021 N. Shepard Street, Anaheim, CA 92806 USA

Sold To Information				
Distributor:			Contact:	Email:
Address:	Notes:			
City, State, Zip:				
Phone:				
Dist PO#:				

End User Information				
End User:			Contact:	Email:
Address:	Notes:			
City, State, Zip:				
Phone:				
Cust PO#	Ship To:			

Tooling Information													
Line#	Mfg.	EDP#	Qty	Diameter	Min Acceptable Diameter	Min Acceptable Length of Cut	Corner Rad. Chamfer Sharp	Corner Rad. Chamfer Size	Chips Acceptable Y/N	End Only Y/N	Coating	Alteration	Alteration Notes / Additional Info
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													

- Some loss in cutting efficiency and/or performance should be expected with reconditioned tools. Additional loss should be expected if not recoated.
 - Due to unequal helix design of Z-Carb type performance end mills, reducing flute length may impact the vibration dampening properties.
1. KSPT will reduce flute length and/or cutting diameter as needed to remove damaged areas, unless specified otherwise. Restricting the minimum acceptable diameter and/or flute length may result in less than 100% removal of damaged areas.
 2. Alterations from original designs will result in additional charges.
 3. Product characteristics not specified by the end user will be manufactured to standard KSPT specifications for similar products.